

bn Nov 29-Dec 5 1994.log

RCS file: /p/cvsroot/c_tests/plumhall/conform.exp,v

Working file: c_tests/plumhall/conform.exp

head: 1.13

branch:

locks: strict

access list:

symbolic names:

plumhall: 1.1.1.2

plumhall5_0: 1.1.1.1

PlumHall: 1.1.1

keyword substitution: kv

total revisions: 15; selected revisions: 1

description:

revision 1.8

date: 1994/11/30 23:55:30; author: claseman; state: Exp; lines: +1 -1

update conform.exp
=====

RCS file: /p/cvsroot/c_tests/plumhall/unixdst/conform/makefile,v

Working file: c_tests/plumhall/unixdst/conform/makefile

head: 1.2

branch:

locks: strict

access list:

symbolic names:

plumhall: 1.1.1.2

plumhall5_0: 1.1.1.1

PlumHall: 1.1.1

keyword substitution: kv

total revisions: 4; selected revisions: 1

description:

revision 1.2

date: 1994/12/01 19:17:01; author: chuck; state: Exp; lines: +3 -3

Changed make variable "LANG" to be "LANG_" instead. The name "LANG" is a poor choice since gmake puts the make variables into the environment, and many implementations of setlocale() will read the environment variable "LANG".
=====

RCS file: /p/cvsroot/calliope/verilog/src/calliope.v,v

Working file: calliope/verilog/src/calliope.v

head: 1.192

branch:

locks: strict

access list:

symbolic names:

keyword substitution: kv

total revisions: 192; selected revisions: 1

description:

Initial checkin

revision 1.192

date: 1994/12/02 19:33:19; author: agc; state: Exp; lines: +11 -9

scaling mode inputs
=====

RCS file: /p/cvsroot/calliope/verilog/src/ci/ci.v,v

Working file: calliope/verilog/src/ci/ci.v

head: 1.33

branch:

bn Nov 29-Dec 5 1994.log

locks: strict

access list:

symbolic names:

keyword substitution: kv

total revisions: 33; selected revisions: 1

description:

n

revision 1.33

date: 1994/12/02 19:32:45; author: agc; state: Exp; lines: +4 -1

missing variable declaration
=====